

# 伍立電線電纜股份有限公司

CABLE SPECIFICATION(線材規格承認書)			
Messrs			
Standard	2468#22 80°C		
	Item (項目)	Unit	Specification (規格值)
	AWG (線規)	AWG	22AWG ( 0.325mm <sup>2</sup> )
	No. of conductor (芯線數)	P.C	-----
Conductor 導體	Material (材質)	-----	Bared Copper Wire (裸銅)
	Filler (填充)	-----	-----
	Construction (結構)	No./mm	0.16/17mm
	Stranded diameter (絞合外徑)	mm	0.8mm
Insulation 絕緣	Material (材質)	-----	-----
	Nom. Thickness (厚度)	mm	-----
	Diameter (線徑)	mm	-----
	Color (顏色)	-----	-----
Electric Characters 電氣特性	Rated temperature (額定溫度)	°C	80°C
	Rated voltage (額定電壓)	V	300V
	Resistance of Insulation (水中常溫絕緣電阻)	MΩ /1000Ft	-----
	Withstand voltage spark (火花試驗)	Kv/Sec	4kv
Jacket 外被	Material (材質)		PVC
	Average thickness (平均厚度)	mm	0.38mm
	Smallest thickness(最小厚度)	mm	0.33mm
	O.D (外徑)	mm	1.7*3.4mm (±0.2)
	Color (顏色)	-----	-----
Marking 印字	E137143 凡 AWM 2468 80°C VW1 2*0.325mm <sup>2</sup> (22AWG) 300V WU-LI LL85694 CSA TYPE AWM A/B 80°C FT1 2*0.325mm <sup>2</sup> (22AWG) 300V WU- LI L.F.		
Configuration: (結構圖) <div style="text-align: center; margin-top: 10px;"> </div>			

核准：

審核：詹景安

製表：陳家美