



Front View

MATERIAL:

- A. COVER: PE+2L
- B. SHELL: ABS
- C. METAL SHIELD: BRASS NICKEL PLATED
- D. HOUSING: NYLON66+GF
- E. CONTACT: BRASS SILVER PLATED

SPECIFICATIONS:

1. RATION: 100V AC 1A MAX OR 12V DC 2A MAX.
2. INSULATION RESISTANCE: 50M OHM MIN at 250V DC.
3. DIELECTRIC STRENGTH: 250V AC / 1 MINUTE.
4. CONTACT RESISTANCE: 30M OHM MAX.
5. INSERTION FORCE: 4.5KG MAX.
6. WITHDRAWAL FORCE: 0.9KG ~ 3KG.
7. OPERATING TEMPERATURE: -20°C ~ 105°C

<p>TOLERANCES</p> <p>.X± 0.1 .XXXX</p> <p>.XX± 0.05 ANGLES</p>		<p>PART NUMBER</p> <p>1102-9</p>	
<p>⌀</p> <p>DRAFT</p> <p>CHECK</p> <p>APPROVAL</p>	<p>mm</p> <p>SCALE</p> <p>DANNY HSU</p>	<p>REV.</p> <p>A</p>	<p>DESCRIPTION</p> <p>9 PIN MINI DIN PLUG ASSY TYPE</p>
<p>DRAFT</p> <p>W.RAY 4/30/12</p>		<p>SHEET</p> <p>1/1</p>	