



| REV | ECN NO. | DESCRIPTION | DRAW | APPD. | DATE |
|-----|---------|-------------|------|-------|------------|
| A | --- | 新版本发行 | SHI | DMX | 2015.11.09 |

- NOTES:
 SPECIFICATION:
 1. CURRENT RATING: 1.5A MAX
 2. VOLTAGE: 100 VAC
 3. TEMPERATURE RANGE: -30 °C ~ 85 °C
 4. CONTACT RESISTANCE: 40 MILLIONHM MAX
 5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
 6. LINSERTION FORCE : 5N~20N
 7. UNMATING FORCE : 8N~20N
 8. DURABILITY: 10,000 CYCLES

| | | | |
|-----|-------------|-----|-------------|
| A1 | QND | B12 | QND |
| A4 | VBUS | B9 | VBUS |
| A5 | CC1 | BB | SBU2 |
| A6 | DP1 | B7 | DN2 |
| A7 | DN1 | BB | DP2 |
| A8 | SBU1 | B5 | CC2 |
| A9 | VBUS | B4 | VBUS |
| A12 | QND | B1 | QND |
| PIN | SIGNAL NAME | PIN | SIGNAL NAME |

| | | | | |
|-----|-----------------|--------------------------|--------------|------|
| 6 | SHELL | STAINLESS STEEL | Ni Plated | 1PCS |
| 5 | SHIELDING PLATE | STAINLESS STEEL | --- | 1PCS |
| 4 | MD | HIGH TEMPERATURE PLASTIC | BLACK | 1PCS |
| 3 | CONTACT | COPPER ALLOY | Au/Ni Plated | 1SET |
| 2 | CONTACT | COPPER ALLOY | Au/Ni Plated | 1SET |
| 1 | HOLDING | HIGH TEMPERATURE PLASTIC | BLACK | 1PCS |
| NO. | DESCRIPTION | MATERIAL | FINISH | QTY |

| | | | |
|------------------|------------|--------------------|----------------------|
| TOLERANCE | | NAME(INTENDED USE) | |
| CUSTOMER DRAWING | | PART NO. | |
| X.X ±0.30 | X' ± 2' | 014101010-017 | |
| XX ±0.20 | XX' ± 1' | | |
| XXX ±0.10 | XXX' ±0.5' | APPD: DMX | DRAWG. NO. 0141-0170 |
| UNITS: mm | | CHEG: TANG | SCALE: 1/1 |
| MATERIAL: / | | DRAW: SHI | SHEET: 1/1 |
| FINISH: / | | | REV: A |