



<b>Rating</b>	16A 125V AC 10A 250V AC
<b>Contact resistance</b>	50mΩ Max
<b>Insulation resistance</b>	DC 500V 100MΩ Min
<b>Dielectric strength</b>	AC 1500V 1 minute
<b>Cut-out</b>	 18.6 6 mm max

FEATURES

- \* MATERIAL: Frame is nylon with glass fiber (UL flame: 94V-2). Terminals are silver plated brass.
- \* Illuminated actuators are molded in PC, available with red, amber, green, blue and white colors.
- \* Mounted by nut.



Ordering number instruction

R13-135 -

FUNCTION		TERMINAL
<b>Different button (按钮不同)</b>		0 2  .187" SQ
<p><b>A</b> </p> <p><b>A 2</b> </p> <p><b>A P</b> </p>		0 9  PC A/C/D/E/F/G/H/I
<b>Illuminated/ Different button (带灯/按钮不同)</b>		1 2  SO A/C/D/E/F/G/H/L
<p><b>B</b> </p> <p><b>B 2</b> </p> <p><b>B 9</b> </p> <p><b>B P</b> </p>		
<b>Different position / Different button (动作特性不同/按钮不同)</b>		
<p><b>C</b> </p> <p><b>C P</b> </p> <p><b>D</b> </p> <p><b>D P</b> </p>		
<b>Momentary (弹回)</b>		
<p><b>E</b> </p> <p><b>F</b> </p> <p><b>G</b> </p> <p><b>H</b> </p>		
<b>I</b>		
<b>Independent circuit (独立电路)</b>		
<p><b>L</b> </p> <p><b>L P</b> </p> <p><b>L F</b> </p>		