

項目 / 型號	YB01A1/YB01A3	YB03A1/YB03A3	YB06A1/YB06A3	YB10A1/YB10A3	
額定電壓	125/250V AC	125/250V AC	125/250V AC	125/250V AC	
額定電流	1A	3A	6A	10A	
洩漏電流	0.8mA MAX 250V,50HZ	0.8mA MAX 250V,50HZ	0.8mA MAX 250V,50HZ	0.8mA MAX 250V,50HZ	
耐電壓	線對線	1450V DC	1450V DC	1450V DC	
	線對地	2250V DC	2250V DC	2250V DC	
絕緣阻抗	100M ohm MIN 250VDC	100M ohm MIN 250VDC	100M ohm MIN 250VDC	100M ohm MIN 250VDC	
直流阻抗	0.5 ohm MAX	0.2 ohm MAX	0.15 ohm MAX	0.1 ohm MAX	
溫度上升	30C MAX	30C MAX	30C MAX	30C MAX	
溫度使用範圍	-25 ~ +85C	-25 ~ +85C	-25 ~ +85C	-25 ~ +85C	
CX	0.1uF Max	0.1uF Max	0.1uF Max	0.1uF Max	
CY	3300pF Max	3300pF Max	3300pF Max	3300pF Max	
電阻	1M/10M ohm	1M/10M ohm	1M/10M ohm	1M/10M ohm	
電感值	3.7mH	1.8mH	0.7mH	0.3mH	
衰減量	NORMAL MODE 25dbMIN	0.50 ~ 45MHZ	0.60 ~ 50MHZ	0.80 ~ 50MHZ	1.20 ~ 50MHZ
	COMMON MODE 25dbMIN	0.10 ~ 40MHZ	0.15 ~ 50MHZ	0.40 ~ 50MHZ	1.40 ~ 50MHZ

衰減量 (0.1uF,3300pF)

COMMON MODE (LINE TO GROUND) IN 50 OHM SYSTEM								
TYPE	CURRENT RATING	FREQUENCY-MHZ						
		0.15	0.5	1.0	5.0	10.0	30.0	
YB01A1/YB01A3	1A	28	38	41	39	39	41	
YB03A1/YB03A3	3A	22	32	36	36	37	38	
YB06A1/YB06A3	6A	14	22	27	38	42	47	
YB10A1/YB10A3	10A	6	14	17	30	36	43	
DIFFERENTIAL MODE (LINE TO LINE) IN 50 OHM SYSTEM								
YB01A1/YB01A3	1A	9	18	24	42	42	41	
YB03A1/YB03A3	3A	8	17	23	38	39	43	
YB06A1/YB06A3	6A	7	16	22	43	43	39	
YB10A1/YB10A3	10A	5	14	18	37	46	41	

線路圖

